

R330M Series

Waterproof 13.56MHZ MF Card
Wiegand Reader



Specifications:

| | |
|-----------------------|---|
| Case Material | Metal |
| Frequency | 13.56MHz |
| Reading Distance | 3.5-5CM |
| Responding Speed | <200ms |
| Wiegand Output | Wiegand 26, Wiegand 34, Wiegand 66 |
| Transmission Distance | 100M |
| Operating Temperature | -10 °C to 60 °C |
| Operating Humidity | 15% to 90% |
| Power Supply | DC 12V |
| Working Current | 44mA-70mA |
| Dimension | 93mm * 93mm * 19mm |
| Net Weight | 220g |
| LED Indicator | Blue (Standby Mode), Green (Reading mode) |
| Cable Outputs | VCC, GND, D0, D1, WG26/34/66, Beep |
| Application | Access Control, Time Attendance, POS, Patrol System, Anti-theft System, etc |

Model Options

| | |
|---------|--|
| R330M-B | Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID |
| R330M-F | Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass |
| R330M-K | Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass, Felica |