

R332M Series

Waterproof Password & 13.56MHZ MF
Card Wiegand Reader



Specifications:

Case Material	Metal
Frequency	13.56MHz
Reading Distance	3.5-5CM
Responding Speed	<200ms
Wiegand Output	Wiegand 26, Wiegand 34, Wiegand 66
Transmission Distance	100M
Operating Temperature	-10 °C to 60 °C
Operating Humidity	15% to 90%
Power Supply	DC 12V
Working Current	44mA-70mA
Dimension	93mm * 93mm * 19mm
Net Weight	150g
LED Indicator	Blue (Standby Mode), Green (Reading mode)
Cable Outputs	VCC, GND, WG0, WG1, WG26/34/66, Control
Application	Access Control, Time Attendance, POS, Patrol System, Anti-theft System, etc

Model Options

R332M-B	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID
R332M-F	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass
R332M-K	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass, Felica