

R350M Series

13.56MHz MF Card Wiegand Reader



Specifications:

Frequency	13.56MHz
Reading Distance	3.5-5CM
Responding Speed	<200ms
Wiegand Output	Wiegand 26(Default), Wiegand 34
Transmission Distance	100M
Operating Temperature	-10 °C to 60 °C
Operating Humidity	20% to 70%
Power Supply	DC 12V
Working Current	About 55mA
Dimension	86mm * 86mm * 18mm
Net Weight	150g
LED Indicator	Blue (Standby Mode), Green (Reading mode)
Cable Outputs	VCC, GND, WG0, WG1, WG26/34, Beep
Application	Access Control, Time Attendance, POS, Patrol System, Anti-theft System, etc

Model Options

R350M-B	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID
R350M-F	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass
R350M-K	Reads ISO/IEC14443A(MF S50,S70,Desfire, NTAG213, NTAG216, Ultralight/FM1204, FM1208) 13.56MHZ, ISO14443B UID, ISO15693, HID iClass, Felica