

# KR Series

Card Readers



KR100-E/M



KR101-E/M



KR102-E/M



KR503-E/M



KR500-E/M



KR501-E/M



KR502-E/M

## RFID/Mifare Card Readers

### Part Numbers

KRxxx-E: 125 KHz Proximity Card Reader

KRxxx-M: 13.56 MHz Mifare Card Reader

### Reading Time

<300ms

### Input Port

External LED Control

External Buzzer Control

### Output Format

E-Models

26bit Wiegand

1's/5's M-Models

Default: 26 bit format

(Optional 34 bit format available)

### Power/Current

6-14V DC/70mA

### LED

Red and Green LEDs

### Beeper

Yes

### Operating Temperature

14F° to 158F° (-10° to +70°C)

### Operating Humidity

10% to 90% relative humidity non-condensing

### Index of Protection

Waterproof IP65

Reverse Polarity Protection

## Dimensions

	KR100 E/M	KR101 E/M	KR102 E/M	KR500 E/M	KR501 E/M	KR502 E/M	KR503 E/M
<b>Height:</b>	4.57in (11.6cm)	3.05in (7.75cm)	3.39in (8.6cm)	4.57in (11.6cm)	3.39in (8.6cm)	3.39in (8.6cm)	4.57in (11.6cm)
<b>Length:</b>	2.95in (7.5cm)	1.69in (4.28cm)	3.39in (8.6cm)	2.95in (7.5cm)	3.39in (8.6cm)	3.39in (8.6cm)	2.95in (7.5cm)
<b>Width:</b>	0.69in (1.75cm)	0.65in (1.65cm)	0.65in (1.63cm)	0.68in (1.73cm)	0.63in (1.6cm)	0.79in (2.0cm)	0.68in (1.73cm)
<b>Weight:</b>	0.35lbs (0.16kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.30lbs (0.14kg)	0.35lbs (0.16kg)



Design and Specifications subject to change without notice

For more info, please visit us or contact us:

[www.isecus.com](http://www.isecus.com)

[sales@isecus.com](mailto:sales@isecus.com)

Whatsapp



Telegram



Wechat

