

KR216 Series

Waterproof Wiegand Card & Password Reader





Specifications:

| Case | ABS material with Mechanical Keyboard |
|-----------------------|--|
| Frequency | KR216E: 125KHZ KR216M: 13.56MHZ KR216EM: 125KHZ & 13.56MHZ |
| Supported Cards | KR216E: ID Card KR216M: Mifare Card like S50, S70, Desfire, Ntag213/216, Ultralight KR216EM=KR216E+KR216M |
| Reading Distance | 3-5CM |
| Responding Speed | <200ms |
| Wiegand Output | Wiegand 26/Wiegand 34 |
| Transmission Distance | 100M |
| Operating Temperature | -20 °C to 65 °C |
| Operating Humidity | 20% to 80% |
| Power Supply | DC 12V |
| Working Current | ≤ 200mA |
| Protection Grade | IP67 (Solid epoxy potted) |
| Dimension | 86mm * 86mm * 16mm |
| Net Weight | 150g |
| LED Indicator | Red (Standby Mode), Green (Reading mode) |
| Cable Outputs | Red(VCC), Black(GND), Green(D0), White(D1), Purple(Beep), Grey(CLED), Yellow(+GND>WG26) |
| Application | Access Control, Time Attendance, POS, Patrol System, Anti-theft System, etc |